

SW-311



Compact subwoofer with stylish finish

Pristine black satin coating complements impeccable design

DCS

Offers easy-to-access front controls to adjust preferences to your suit your listening needs

ARC II

Automatically customizes optimal bass performance for any room

Passive non-resonant woven fiberglass drivers

Produce tight musical bass

BASH® Digital Hybrid Class AB Amplifier

Efficiently produces reliable, high-powered sound

4-layer aluminum-wound voice coil

Provides enhanced low-end output

1-watt standby mode

Energy-saving feature

Powerful and efficient bass extension is at the heart of every Klipsch subwoofer. Crafted to effortlessly integrate and perform with any brand or speaker model, our new compact subwoofer models are here to produce the mind-blowing sound Klipsch is known for in any home.

KLIPSCH BELIEVES FOUR PRINCIPLES TO BE THE FOUNDATION FOR GREAT SOUND:

- **HIGH EFFICIENCY:** Every Klipsch speaker is horn-loaded because the horn shape is perfect for accurate and dynamic sound transmission. Greater efficiency means lower distortion which means maximum realism.
- **DYNAMIC RANGE:** Klipsch horn technology reproduces the softest sounds with remarkable clarity and detail and the loudest sounds with no harshness or distortion. That's what's known as the best of both worlds.
- **CONTROLLED DIRECTIVITY:** Unique Klipsch horn technology means speakers that more accurately direct sound. The result is a more lifelike soundstage and way more "Whoa - Did you hear that?"
- **Flat Frequency Response:** We believe in delivering exactly the sound artists intend. Hence, Klipsch's stunningly accurate speakers - with no unnatural highs, mids or lows.

SPECIFICATIONS	SW-311
Frequency Response	22Hz-120KHz ± 3dB
Sensitivity	106dB @ 40Hz
Maximum Acoustic Output	118dB @ 30Hz
Amplifier Type	BASH Digital Hybrid class-AB
Amplifier Power	FTC Rated Power: 500 watts continuous @ <2% THD / Dynamic Power*: 1200 watts
Driver Components	10" (25.4cm) Active / Dual 10" Passive non-resonant Woven Fiberglass drivers
Enclosure Type	Bass-reflex via dual side-firing passive radiators
Inputs	L/R Line-level RCA jacks, USB, 12V Trigger, MIC, WA port
Outputs	Line-level RCA jack
Height	13" (33cm)
Width	13" (33cm)
Depth	14" (35.6cm)
Weight	37lbs (16.8kg)
Features	DCS control and feature set w/ 5 system presets and Adaptive Room Correction II with 12 active filters
Finish	Black satin
Voltage	100-120V / 220-240V~50/60Hz 5A (Auto-voltage switching) with 1 Watt standby
Export Version	NA, EU
Built From	2010