

COOLPIX COMPARISON GUIDE



Product Number	Black 25580	Black 25593	Black 25583	Slate Black 25594	Graphite Black 26108 Cool Blue 26109 Plum 26110
Effective Megapixels	12.1 million	8.1 million	8.1 million	10.0 million	10.0 million
Lens	3.5x Zoom-NIKKOR; 7.5-26.3mm (35mm [135] format picture angle: 35-123mm); f/2.7-5.3; 7 elements in 6 groups; Digital zoom: up to 4x (35mm [135] format picture angle: 492mm)	5x Zoom-NIKKOR; 6.4-32mm (35mm [135] format picture angle: 36-180mm); f/3.6-4.5; 9 elements in 7 groups; Digital zoom: up to 4x (35mm [135] format picture angle: 720mm)	3.6x Zoom-NIKKOR; 4.7-17mm (35mm [135] format picture angle: 28-102mm); f/2.8-5.6; 7 elements in 6 groups; Digital zoom: up to 4x (35mm [135] format picture angle: 408mm)	4x Zoom-NIKKOR; 5.0-20mm (35mm [135] format picture angle: 28-112mm); f/2.7-5.8; 7 elements in 6 groups; Digital zoom: up to 4x (35mm [135] format picture angle: 448mm)	5x Zoom-NIKKOR; 6.3-31.5mm (35mm [135] format picture angle: 36-180mm); f/3.5-5.6; 8 elements in 6 groups; Digital zoom: up to 4x (35mm [135] format picture angle: 720mm)
Focus range (from lens)	1 ft. (30cm) to infinity (∞); Macro close-up mode: 1.6 in. (4cm) to infinity (∞)	1 ft. 4 in. (40cm) to infinity (∞); Macro close-up mode: 4 in. (10cm) to infinity (∞)	1 ft. 7.7 in. (50cm) to infinity (∞); Macro close-up mode: 1.9 in. (5cm) to infinity (∞)	1 ft. 7.7 in. (50cm) to infinity (∞); Macro close-up mode: 1.2 in. (3cm) to infinity (∞) at wide-angle	1 ft. 2 in. (35cm) to infinity (∞); Macro close-up mode: 4 in. (10cm) to infinity (∞) at wide-angle
Monitor	2.5-in., approx. 230k-dot, wide viewing angle TFT LCD with anti-reflection coating	2.5-in., approx. 153k-dot, TFT LCD, Electronic Viewfinder	2.4-in., approx. 115k-dot, TFT LCD	2.7-in., approx. 230k-dot, wide viewing angle TFT LCD with anti-reflection coating	2.5-in., approx. 230k-dot, wide viewing angle TFT LCD with anti-reflection coating
Storage media	Internal memory (approx. 52 MB), SD memory cards	Internal memory (approx. 12 MB), SD memory cards	Internal memory (approx. 52 MB), SD memory cards	Internal memory (approx. 45 MB), SD memory cards	Internal memory (approx. 50 MB), SD memory cards
ISO sensitivity	ISO 64, 100, 200, 400, 800, 1600, 2000, 3200*2, Auto (auto gain ISO 64-800)	ISO 80, 100, 200, 400, 800, 1600, 2000, Auto (auto gain ISO 80-800)	ISO 64, 100, 200, 400, 800, 1600, 2000, Auto (auto gain ISO 64-1000)	ISO 100, 200, 400, 800, 1600, 3200, Auto (auto gain ISO 100-800), High-Sensitivity mode (ISO 100-2000)	ISO 64, 100, 200, 400, 800, 1600, 2000, Auto (auto gain ISO 64-800), High-Sensitivity mode (ISO 64-1600)
Power sources	Rechargeable Li-ion Battery EN-EL5 (supplied), AC Adapter EH-62A (optional)	Two AA alkaline (supplied), lithium or oxyride batteries, AC Adapter EH-65A (optional)	Two AA alkaline (supplied), lithium or oxyride batteries, AC Adapter EH-65A (optional)	Rechargeable Li-ion Battery EN-EL10 (supplied), AC Adapter EH-62D (optional)	Rechargeable Li-ion Battery EN-EL11 (supplied), AC Adapter EH-62E (optional)
Battery life	Approx. 240 shots with EN-EL5 battery	Approx. 190 shots with alkaline batteries	Approx. 140 shots with alkaline, 580 shots with lithium	Approx. 190 shots with EN-EL10 battery	Approx. 200 shots with EN-EL11 battery
Dimensions (WxHxD)	Approx. 3.9 x 2.5 x 1.6 in. (98 x 64.5 x 41 mm) excluding projections	Approx. 3.8 x 2.5 x 1.4 in. (95.5 x 63.5 x 36 mm) excluding projections	Approx. 3.8 x 2.6 x 1.8 in. (94.5 x 66 x 44 mm) excluding projections	Approx. 3.5 x 2.1 x 0.9 in. (88.5 x 53 x 22.5 mm) excluding projections	Approx. 3.6 x 2.1 x 0.9 in. (90 x 53.5 x 22 mm) excluding projections
Weight	Approx. 7.1 oz. (200 g) without battery and SD memory card	Approx. 5.6 oz. (160 g) without battery and SD memory card	Approx. 5.6 oz. (160 g) without battery and SD memory card	Approx. 4.6 oz. (130 g) without battery and SD memory card	Approx. 4.2 oz. (120 g) without battery and SD memory card

All products indicated by trademark symbols are trademarked and/or registered by their respective companies. Specifications and equipment are subject to change without any notice or obligation on the part of the manufacturer.
©2008 Nikon Inc. 1-800-NIKON-UX nikonusa.com



Product Number	Graphite Black 26112	Graphite Black 26100 Cool Blue 26101 Brushed Bronze 26102 Plum 26103	Silver 25575	Black 25574	Navy Blue 25596 Ruby Red 25597	Black 25598
Effective Megapixels	8.0 million	8.0 million	8.1 million	8.1 million	8.0 million	7.1 million
Lens	3x Zoom-NIKKOR; 5.7-17.1mm (35mm [135] format picture angle: 35-105mm); f/2.8-4.7; 5 elements in 5 groups; Digital zoom: up to 4x (35mm [135] format picture angle: 420mm)	3x Zoom-NIKKOR; ; 6.3-18.9mm (35mm [135] format picture angle: 38-114mm); f/3.1-5.9; 6 elements in 5 groups; Digital zoom: up to 4x (35mm [135] format picture angle: 456mm)	3x Zoom-NIKKOR; 6.3-18.9mm (35mm [135] format picture angle: 38-114mm); f/3.3-4.2; 12 elements in 9 groups; Digital zoom: up to 4x (35mm [135] format picture angle: 456mm)	3x Zoom-NIKKOR; 6.3-18.9mm (35mm [135] format picture angle: 38-114mm); f/3.3-4.2; 12 elements in 9 groups; Digital zoom: up to 4x (35mm [135] format picture angle: 456mm)	3x Zoom-NIKKOR; 5.7-17.1mm (35mm [135] format picture angle: 35-105mm); f/2.8-4.7; 5 elements in 5 groups; Digital zoom: up to 4x (35mm [135] format picture angle: 420mm)	3x Zoom-NIKKOR; 5.7-17.1mm (35mm [135] format picture angle: 35-105mm); f/2.8-4.7; 5 elements in 5 groups; Digital zoom: up to 4x (35mm [135] format picture angle: 420mm)
Focus range (from lens)	1 ft. 7.7 in. (50cm) to infinity (∞); Macro close-up mode: 5.9 in. (15cm) to infinity (∞)	2 ft. (60cm) to infinity (∞); Macro close-up mode: 4 in. (10cm) to infinity (∞)	1 ft. (30cm) to infinity (∞), Macro close-up mode: 1.6 in. (4cm) to infinity (∞)	1 ft. (30cm) to infinity (∞), Macro close-up mode: 1.6 in. (4cm) to infinity (∞)	1 ft. 7.7 in. (50cm) to infinity (∞); Macro close-up mode: 5.9 in. (15cm) to infinity (∞)	1 ft. 7.7 in. (50cm) to infinity (∞); Macro close-up mode: 5.9 in. (15cm) to infinity (∞)
Monitor	2.5-in., approx. 153k-dot, TFT LCD with anti-reflection coating	2.5-in., approx. 230k-dot, wide viewing TFT LCD with anti-reflection coating	3.0-in., approx. 230k-dot, wide viewing angle TFT LCD with anti-reflection coating	3.0-in., approx. 230k-dot, wide viewing angle TFT LCD with anti-reflection coating	3.0-in., approx. 230k-dot, TFT LCD	2.8-in., approx. 230k-dot, TFT LCD
Storage media	Internal memory (approx. 23 MB), SD memory cards	Internal memory (approx. 52 MB), SD memory cards	Internal memory (approx. 13 MB), SD memory cards	Internal memory (approx. 13 MB), SD memory cards	Internal memory (approx. 21 MB), SD memory cards	Internal memory (approx. 21 MB), SD memory cards
ISO sensitivity	ISO 64, 100, 200, 400, 800, 1600, 2000, Auto (auto gain ISO 64-1600)	ISO 64, 100, 200, 400, 800, 1600, 2000, Auto (auto gain ISO 64-800), High-Sensitivity mode (ISO 64-1600)	ISO 100, 200, 400, 800, 1600, Auto (auto gain ISO 100-800)	ISO 100, 200, 400, 800, 1600, Auto (auto gain ISO 100-800)	Auto (auto gain ISO 64-1600)	Auto (auto gain ISO 64-1600)
Power sources	Rechargeable Li-ion Battery EN-EL10 (supplied), AC Adapter EH-62D (optional)	Rechargeable Li-ion Battery EN-EL10 (supplied), AC Adapter EH-62D (optional)	Rechargeable Li-ion Battery EN-EL8 (supplied), AC Adapter EH-64 (supplied)	Rechargeable Li-ion Battery EN-EL8 (supplied), AC Adapter EH-64 (supplied)	Two AA alkaline (supplied), lithium or oxyride batteries, AC adapter EH-65A (optional)	Two AA alkaline (supplied), lithium or oxyride batteries, AC adapter EH-65A (optional)
Battery life	Approx. 200 shots with EN-EL10 battery	Approx. 220 shots with EN-EL10 battery	Approx. 150 shots with EN-EL8 battery	Approx. 150 shots with EN-EL8 battery	Approx. 180 shots with alkaline, 650 shots with lithium	Approx. 180 shots with alkaline, 650 shots with lithium
Dimensions (WxHxD)	Approx. 3.7 x 2.1 x 0.9 in. (94 x 53 x 22.5 mm) excluding projections	Approx. 3.6 x 2.2 x 0.7 in. (90 x 55.5 x 18 mm) excluding projections	Approx. 3.8 x 2.3 x 0.8 in. (97.5 x 59 x 21 mm) excluding projections	Approx. 3.6 x 2.3 x 0.8 in. (92.5 x 59 x 21 mm) excluding projections	Approx. 3.7 x 2.4 x 1.2 in. (95 x 61 x 29.5 mm) excluding projections	Approx. 3.7 x 2.4 x 1.2 in. (95 x 61 x 29.5 mm) excluding projections
Weight	Approx. 4.1 oz. (115 g) without battery and SD memory card	Approx. 3.5 oz. (100 g) without battery and SD memory card	Approx. 4.4 oz. (125 g) without battery and SD memory card	Approx. 4.4 oz. (125 g) without battery and SD memory card	Approx. 4.4 oz. (125 g) without battery and SD memory card	Approx. 4.4 oz. (125 g) without battery and SD memory card

*1 Based on CIPA industry standard for measuring life of camera batteries. Measured at 73 degrees F (23 degrees C); zoom adjusted with each shot, built-in flash fired with every other shot, image mode set to Normal.
*2 ISO 3200 is available only for image sizes of 5M (2592 x 1944) or smaller



Left: ©Dan Monakil, Right: ©Dan Monakil



Left: ©Joe McNally, Right: ©Dan Monakil