PXC 310/PXC 310 BT Noise Cancelling Headphones

Frequent travelers can finally have it all: aggressive noise cancelling, compact size, highfidelity audio and options to listen wirelessly. Featuring NoiseGard™ 2.0 technology, the PXC 310 and PXC 310 BT reduce up to 90% of ambient noise and offer a convenient TalkThrough function. Perfect for your next adventure in the skies.





PXC 310

- Reduces up to 90% of ambient noise
- TalkThrough function permits chatting with seatmates without removing the headphones
- Collapsible, metal-reinforced headband with simple folding mecha-
- Intelligent, easy-to-use operating interface
- Neodymium magnets and Duofol diaphragms provide high-fidelity sound reproduction
- Optimized for in-flight entertainment systems (aircraft adapters) included) and portable media devices
- Extensive accessories included: in-flight adapters, multi-country recharger, rechargeable Lithium-Polymer battery and carrying case

PXC 310 BT

- Same specifications as the PXC 310
- Bluetooth® 2.1 digital wireless reception technology (listen only) compatible with countless Bluetooth enabled digital audio devices
- Supports apt-X[®]: sophisticated audio compression technology for true hi-fi quality
- Sennheiser BTD 300 Bluetooth dongles provide apt-X and Bluetooth audio transmission on-demand (sold separately)
- Works as a wired headphone without NoiseGard or Bluetooth activated

The Bluetooth® word mark and logo are registered trademarks and are owned by the Bluetooth SIG, Inc. apt-x and the apt-x logo are trademarks or registered trademarks of APT Ltd.



PXC 310



PXC 310 BT

Specifications

Model	PXC 310	PXC 310 BT
EAN No.	4044156027302	4044156027289
UPC No.	615104140165	615104140141
Cat. No.	502386	502384
Design	Premium collapsible mini-headphones	
Transducer principle	Dynamic, closed	
Ear coupling	On-the-ear	
Frequency response	15-22,000 Hz	
Nominal impedance active/passive	590/100 Ω	
SPL	107 dB SPL	
THD at 1 kHz	< 0.1%	
Operating time NoiseGard	≤ 20 hrs	≤ 20 hrs
Operating time Bluetooth®		≤ 12 hrs
Operating time Bluetooth® + NoiseGard		≤ 8 hrs
NoiseGard active noise reduction	23 dB	
Passive noise attenuation	25 dB	
Weight	3.7 ounces	
Cable length		
Audio cable	4.6 ft	
Charging cable	3.9 ft (USB)	
Audio connector	1/8" (3.5 mm) stereo jack plug	
Inflight adapters	1/8" (3.5 mm) double mono jack plug, 1/4" (6.3 mm) stereo jack plug	
Bluetooth®		Version 2.1+ EDR
Range		up to 33 ft.
Protocols		A2DP, AVRCP
Codec		SBC, apt-X
Packaging		
Design	Reclosable window cardboard box	
Packaging dimensions (W x H x D)	7.5 x 3.3 x 7.9 inches	
Master carton dimensions (W x H x D)	18.5 x 17.7 x 9.3 inches	
Units per master carton	10 units	
Languages	German, English, French, Spanish, Italian, Dutch, Portuguese	
Delivery includes	Detachable audio cable (2.5 mm to 3.5 mm jack plug), in-flight audio adapter (3.5 mm double mono jack), 1/4" (6.3 mm) audio adapter, USB charging cable, multi-country wall charging adapter, rechargeable Lithium Polymer battery (BA 370), carrying case	