



NILES®



PB6Si

STEREO INPUT PLANTER BOX LOUDSPEAKER



Planter Box Style Indoor/Outdoor Stereo Input Loudspeaker

- Designed to hold live plants
- Stereo Input or mono mode
- Dual, Bridge-mounted, Teteron® tweeters, mounted at a custom angle for optimum dispersion

SPECIFICATIONS SHEET

6 INCH WEATHERPROOF PLANTER BOX LOUDSPEAKER

PB6Si

Stock Numbers

FG01463 Weathered Concrete

FG01462 Terracotta



Features

- Artistically crafted cabinet with shaped MicroPerf™ aluminum grilles looks natural and realistic
- 6.5" dual voice coil injection-molded TCC™ (talc, carbon, and ceramic) filled polypropylene woofer with butyl rubber surround
- Dual 1" fluid-cooled tri-laminate Teteron® tweeters mounted at a custom angle for optimum dispersion
- Separate left and right channel inputs provide stereo sound in a single loudspeaker projecting quality stereo sound over a larger area than conventional loudspeakers
- Weatherproof design ensures performance outdoors
- Designed to accommodate live plants
- Dual 3-foot burial-rated connection cables with waterproof wire-nuts to ensure trouble free connection
- Can be wired in one-speaker stereo-input mode or two-speaker stereo mode
- Impedance: 8 ohm in one-speaker stereo-input mode or 4 ohm in two-speaker stereo mode
- Recommended amplifier power: 10W to 100W
- Dimensions: 28" wide x 12 1/2" high x 11 1/2" deep
71.1 cm wide x 31.8 cm high x 29.2 cm deep
- Weight: 35 lbs. (15.9 kgs)

Warranty: Lifetime Limited Warranty

PRODUCT DETAILS

Recommended Amplifier Power

10 to 100 Watts

Nominal Impedance

8 Ohm, in one-speaker stereo input mode

4 Ohm, in two-speaker stereo mode

Wiring Requirements

2-conductor direct burial cable at the following sizes depending on longest length of cable required (2 per speaker in one-speaker stereo mode):

Wire Gauge	Maximum Distance
16	60 ft (18 m)
14	100 ft (30 m)
12	160 ft (50 m)

Temperature Extremes

-50° to 185° Fahrenheit

-45° to 85° Celsius

